



Technical Data Sheet		NITTA BELT POLY		
		Belt type	M-1000GS	
P-035		• Tangential belt for O.E. Machines		
Applications				
Item	Description		Remarks	
Specification	Construction			①NBR (Ground surface, Blue) ②PA Fabric ③PA Film ④NBR (Ground surface, Black)
	Antistatic	Yes		
Dimensions	Width	6 to 325 [mm]		
	Length	500 to 105,000 [mm]		
	Thickness	2.6 [mm]		
	Joint	Skived joint Adhesive Polybond A and E		
	Tensile strength	390 [N/mm]		Test speed: 50mm/min
Properties	Elongation at break	20 [%]		Ambient condition: 23°C,50%R.H.
	Standard elongation	2 [%]		
	Tension at 2 [%]	19.5 [N/mm]		Ambient condition: 23°C,50%R.H.
	Minimum pulley dia.	100 [mm]		
	Operating temp.	-20 to +80°C		
	Coefficient of friction	0.5 to 0.6(Steel) (Blue side)		Measurement condition: 7kPa, 1mm/s
		0.5 to 0.6(Steel) (Black side)		Ambient condition: 23°C,50%R.H.
Mass	2.9 [kg/m ²]			
Features				

Industrial Products Div.