

Technical Datasheet	SEB™ Belt type	SE-F50-SBU	SF-014 ver.1
----------------------------	-------------------	-------------------	--------------

Applications

- Low-load transmission and conveyance
- Automatic ticket gate
- Ticket machine
- Banknote conveyor

Construction



Impregnated side	Ground side
Millable urethane rubber	Millable urethane rubber
Black	Black

*Depending on application, both sides can be used.

Tension member	Splice
Polyester	Seamless
Seamless fabric	

Construction 



Dimensions

Width	5~200mm
Length	96.5~1560mm <small>*Depending on mold size</small>
Standard thickness	0.8mm
Range of thickness	-
Weight	0.8 kg/m ²

Please contact Nitta if you need other dimensions.

Regulatory compliance

RoHS(2011/65/EC),(EU)2015/863)

Features

- Antistatic
- Abrasion resistance
- Crack resistance
- Oil resistance

Properties

Dynamic properties

Standard elongation	2.0%
Tension after relaxation at 2.0%	2.5N/mm
Operation temperature range	-20~60°C

Minimum pulley diameter

When of standard thickness	10mm
----------------------------	------

Tensile properties

Tensile strength	24.5N/mm
Elongation at break	13%
Maximum allowable elongation	1.0~3.0%

Coefficient of friction

Impregnated side vs. Paper	0.3~0.6
Ground side vs. Steel	0.4~0.8