


<b>Technical Datasheet</b>	<i>PolySprint™</i> Belt type <b>SNTC-RB22A</b>	Conveyor Belt PS-077 Ver.5
----------------------------	---	-------------------------------

**Applications**


- Belt on roller / MDR
- Logistics
- Light duty conveyor

**Construction**


Top side	Bottom side
Soft TPU	-
RB pattern	Knit
Green	Blue

Tension member	Splice
-	Finger
Knit	(10×30, 20×20)

Construction


**Dimensions**

Width/Roll (max.)	1030mm
Width/Endless (max.)	1030mm
Length (max.)	50m
Total thickness	2.25mm
Weight	2.0 Kg/m <sup>2</sup>

Please contact Nitta if you need other dimensions.

**Regulatory compliance**

 RoHS(2011/65/EC,  
 (EU)2015/863)

**Features**

- Antistatic
- No tensioning device required
- High grip
- Incline conveyance
- Whisper
- Slider bed
- Roller bed
- Easy splice with NITTA tool

**Properties**
**Minimum pulley diameter**

Flexing	25mm
Finger	25mm
Back flexing	25mm
Finger	25mm

**Dynamic properties**

Standard elongation	2.0%
Tension after relaxation at 2.0% *	0.3N/mm
Initial tension at 8.0%	2.6N/mm
Tension after relaxation at 8.0% *	1.3N/mm
Operating temperature range	-20~60°C

\*After 200hrs running-in

**Tensile properties**

Tensile strength	15N/mm
Elongation at break	150%
Maximum allowable tension	2.6N/mm
Maximum allowable elongation	8.0%

**Coefficient of friction**

Top	vs. Steel	0.9~1.0
	vs. Paper	approx.1.0
Bottom	vs. Steel	0.1~0.2
	vs. Paper	0.2~0.3
	vs. Lagged pulley	0.3~0.5
	vs. POM (resin)	0.1~0.3